

LX Interview Room Recording System Accessories - Audio

PZM Microphone-Tubular Featuring 3/4" tubular housing for ceiling or wall installations and low frequency attenuation below the voice range to reduce pickup of HVAC rumble. XLR connector, phantom powered.



PZM Microphone-Plate Featuring standard "light switch" wall plate mounting and low frequency attenuation below the voice range to reduce pickup of HVAC rumble. Screw terminals, phantom powered.



PZM Microphone-Stainless Security Featuring a moisture resistant microphone element housed in an inconspicuous stainless steel enclosure for high security or jail applications. Low frequencies below the voice range are attenuated to reduce the pickup of HVAC rumble. Screw terminals, phantom powered.



Microphone Pre-Amp/Compressor-Mono Single channel microphone pre-amplifier with volume control, audio level metering and phantom power. The compressor controls overload and clipping over a wide dynamic range of input signal levels.



Microphone Pre-Amp/Compressor-Stereo Dual channel microphone pre-amplifier with volume control, audio level metering and phantom power. The compressor controls overload and clipping over a wide dynamic range of input signal levels.



Balanced/Shielded XLR Audio Cable Constructed with two-conductor, shielded, vinyl jacketed, broadcast type cable with hand soldered locking XLR connectors.

